

# Antifouling remover

---

## FEATURES

ANTIFOULING STRIPPER is a highly effective remover for antifouling layers. Within a short time, these layers are dissolved to the point where they can easily be removed with a spatula. Due to its gel-like consistency, the product adheres well to vertical surfaces without dripping. Additionally, ANTIFOULING STRIPPER does not affect gelcoat or 2-component primers, making it ideal for use on various substrates.

## APPLICATION

Suitable for removing all types of antifouling paints from GRP, wood, steel, and aluminum surfaces.

## PRODUCT DATA

- **Content:** 2.5 liters
- **Color:** Transparent
- **Density:** 1.0 g/cm<sup>3</sup>
- **Consumption:** approx. 200-600 ml/m<sup>2</sup>, depending on the thickness of the old paint layer

## PROCESSING

Apply ANTIFOULING STRIPPER evenly with a broad brush on the surface to be treated. Allow the product to work for 60 minutes to a maximum of 2 hours. Then, remove the dissolved layers with a spatula. Repeat the process if necessary until all paint layers are removed. Ensure that the paint residues are collected and disposed of in an environmentally friendly manner. Protect adjacent surfaces from possible damage. Always wear safety gloves and goggles. After use, thoroughly rinse the surface with water to remove any remaining residue. Ensure the surface is completely dry before applying a new paint layer. Apply the product at temperatures between +5°C and +25°C.

## PRECAUTIONS

For information on handling the products and disposal, please refer to the valid safety data sheet and the relevant information sheets of the Chemical Industry Employers' Liability Insurance Association. The above information, particularly the suggestions for processing and using our products, is based on our knowledge and experience under normal conditions. Due to

the different materials, substrates, and varying working conditions, no guarantee of a work result or liability, regardless of the legal relationship, can be derived from these instructions or from oral advice unless intent or gross negligence can be attributed to us. The user must prove that they have transmitted all the necessary knowledge required for proper and successful evaluation in writing, timely, and completely to us. Third-party rights must be observed. Furthermore, our respective sales and delivery conditions apply. The latest technical data sheet, which should be requested from us, applies.

**Copyright VOSSCHEMIE**

[www.yachtcare.de](http://www.yachtcare.de)

September 2011-1