

Teak oil 3

FEATURES

TEAK BRIGHTENER 2 is both a cleaner and a brightener for weathered and grayed wood. It penetrates deeply into the surface, cleaning the pores thoroughly. It does not bleach or damage the wood but restores its natural, rich color. The use of TEAK BRIGHTENER 2 is gentle on materials, as the teak does not need to be sanded. Paint, glue joints, or seals are not damaged during the cleaning process.

APPLICATION AREA

- **Cleaner:** Deeply cleans wood pores from weather-related dirt.
- **Brightener:** Restores the wood color without sanding.
- **Color Refresher:** Restores the wood to a natural, warm tone.

PRODUCT DATA

- **Packaging:** 1,0 L
- **Color:** Bluish
- **Consumption:**
 - For heavily grayed wood, undiluted: approx. 200 ml/m²
 - For cleaning, diluted with water at a 1:5 ratio: approx. 50 ml/m²

PROCESSING

The wood surface should be thoroughly wetted with water. Apply TEAK BRIGHTENER 2 generously and lightly rub it in with a brush (synthetic bristles are recommended). The exposure time is about 10 to 20 minutes. Do not let the cleaner dry; keep it moist with water if necessary. After 20 minutes of exposure, the gel-like substance should be removed by brushing with plenty of water or using a pressure washer.

For brightening, TEAK BRIGHTENER 2 is used concentrated; for refreshing or cleaning, it is diluted at a 1:5 ratio with water. In cases of severe discoloration, the process may need to be repeated. Allow the wood to dry completely (at least 2 to 3 days). If necessary, the treated surface can be smoothed with sandpaper (grit 100 or finer) along the wood grain. Then treat with TEAK OIL 3 for protection and care.

Caution: Do not transfer TEAK BRIGHTENER 2 into metal containers. Do not allow it to sit on metal surfaces for extended periods; if contact occurs, rinse with plenty of fresh water. The tools used can be cleaned with water and soap.

PRECAUTIONS

For information on handling the products and disposal, please refer to the current safety data sheet and the relevant bulletins from the Chemical Industry Association. The above information, particularly the suggestions for processing and use of our products, is based on our knowledge and experience in standard cases. Due to the variety of materials, substrates, and different working conditions, a guarantee of a work result or liability, regardless of the legal basis, cannot be derived from these instructions or from any oral advice, unless we are guilty of intent or gross negligence.

The user must prove that he has provided us in writing with all knowledge necessary for proper and successful evaluation in a timely and complete manner. Third-party rights must be observed. Otherwise, our respective sales and delivery conditions apply. The latest technical data sheet should be requested from us.

Copyright VOSSCHEMIE
www.yachtcare.de
Maart 2018 – 1